

Referer

Referrer's Description

While application start option referrer will be transferred. In this option you can set what URL to use after exit application.

For correct return from page transition to application should be made, is necessary to use parameter **referrer**.

While loading application in GET, referrer is automatically added (it will contain urlencoded address that will be used on exit from application.)

For using referrer there is a need to decode it in first place (function decodeURIComponent)

Application start:

```
http://example.com/example-app/?referrer=http%3A%2F%2Fexample2.com.ua%2Finet-services%2Ftest_html%2F%3Flanguage%3Dru
```

Decoded referrer in this example is

```
http://example2.com.ua/inet-services/test_html/?language=ru
```

Method of getting GET parametrs:

```
var _GET = (function(){  
    var url = window.location.href;  
    var x = url.indexOf('?');  
    var get = {};  
    if (x!=-1){  
        var l = url.length;  
        url= url.substr(x+1, l-x);  
        l = url.split('&');  
        x = 0;  
        for(var i in l){  
            if (l.hasOwnProperty(i)){
```

```
        url= l[i].split('=');  
  
        get[url[0]] = decodeURIComponent(url[1]);  
  
        x++;  
    }  
}  
}  
  
return get;  
})();
```

From:
<https://docs.infomir.com.ua/> -

Permanent link:
https://docs.infomir.com.ua/doku.php?id=en:stb_webkit:faq:referer

Last update: **2019/05/17 11:23**

