

ESW-16

- [Документация](#)
- [ПО \(Firmware\)](#)
- [SNMP mibs](#)

Пример конфигурации

```
config ip ip "10.90.90.90" netmask "255.0.0.0" gateway "0.0.0.0" ip-method
manual vid 1 host-name "ESW-16"
config advanced igmp-snooping enabled queue-mode wrr-all age-time 300
create user-accounts-sys username "Admin" access-type admin hash
"7c40cb219e1e59020a8c72754e2bf7245d4646e7" hash2
"c85f499d5507bf18534a6c8f21210751"
config user-profile username "Admin" cli-color enabled cli-page-control
disabled
config syslog status disabled facility local-0 prio-remap-debug debug prio-
remap-error err prio-remap-info info prio-remap-notice notice prio-remap-
warning warning
create vlans 1 name "Default VLAN" override-priority disabled priority-value
0
config vlans 1 add-untagged ports 1-18
create vlans 4094 name "rocco" override-priority disabled priority-value 0
config vlans 4094 add-tagged ports 18
config igmp-snooping 1 state disabled querier-state v2 robustness 2 interval
125 max-response 10
config igmp-snooping 1 set-port-auto ports 1-18
config igmp-snooping 4094 state disabled querier-state v2 robustness 2
interval 125 max-response 10
config igmp-snooping 4094 set-port-auto ports 1-18
config ports-forwarding 1 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 2 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 3 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 4 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 5 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 6 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 7 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 8 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 9 learning enabled sa-mac-checking disabled forward-
unknown enabled group-addr-filtering forward-all
config ports-forwarding 10 learning enabled sa-mac-checking disabled
```

```
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 11 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 12 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 13 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 14 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 15 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 16 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 17 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config ports-forwarding 18 learning enabled sa-mac-checking disabled
forward-unknown enabled group-addr-filtering forward-all
config 802-lq 1 pvid 1 force-default-vid disabled mode disabled
config 802-lq 2 pvid 1 force-default-vid disabled mode disabled
config 802-lq 3 pvid 1 force-default-vid disabled mode disabled
config 802-lq 4 pvid 1 force-default-vid disabled mode disabled
config 802-lq 5 pvid 1 force-default-vid disabled mode disabled
config 802-lq 6 pvid 1 force-default-vid disabled mode disabled
config 802-lq 7 pvid 1 force-default-vid disabled mode disabled
config 802-lq 8 pvid 1 force-default-vid disabled mode disabled
config 802-lq 9 pvid 1 force-default-vid disabled mode disabled
config 802-lq 10 pvid 1 force-default-vid disabled mode disabled
config 802-lq 11 pvid 1 force-default-vid disabled mode disabled
config 802-lq 12 pvid 1 force-default-vid disabled mode disabled
config 802-lq 13 pvid 1 force-default-vid disabled mode disabled
config 802-lq 14 pvid 1 force-default-vid disabled mode disabled
config 802-lq 15 pvid 1 force-default-vid disabled mode disabled
config 802-lq 16 pvid 1 force-default-vid disabled mode disabled
config 802-lq 17 pvid 1 force-default-vid disabled mode disabled
config 802-lq 18 pvid 1 force-default-vid disabled mode disabled
config ports-description 1 description "default name"
config ports-description 2 description "default name"
config ports-description 3 description "default name"
config ports-description 4 description "default name"
config ports-description 5 description "default name"
config ports-description 6 description "default name"
config ports-description 7 description "default name"
config ports-description 8 description "default name"
config ports-description 9 description "default name"
config ports-description 10 description "default name"
config ports-description 11 description "default name"
config ports-description 12 description "default name"
config ports-description 13 description "default name"
config ports-description 14 description "default name"
```

```
config ports-description 15 description "default name"
config ports-description 16 description "default name"
config ports-description 17 description "default name"
config ports-description 18 description "default name" "Zhukova 4d" system-
contact "infomir" system-name "esw-test"
create snmp-com2sec sec-name "testuser" ip-subnet 10.90.90.0/24 com-name
"public"
create snmp-group group-name "testgroup" security-model any security-name
"testuser"
create snmp-view view-name "all" view-type included oid ".1"
create snmp-access group-name "testgroup" context-name "" security-model any
security-level no-auth read-view "all" write-view "all" notify-view "all"
config storm-control measure-interval 5000 cooldown-interval 30000
config storm-ports-ctl 1-18 trap-status disabled uc-limit 1000 uc-action
ignore bc-limit 1000 bc-action ignore mc-limit 1000 mc-action ignore
config sensors relay 0
disable syslog
enable snmp
enable cli
enable web
```

From:

<https://docs.infomir.com.ua/> -

Permanent link:

https://docs.infomir.com.ua/doku.php?id=knowledge_base:esw16_generalinfo_config

Last update: **2021/12/15 15:08**

